

07B Power Wash Steel

Thermoplastic hose with steel reinforcement for water cleaning applications

From 210 to 280 bar (3000 to 4000 psi)



FEATURES

Inner Tube

Thermoplastic polymer

Reinforcement

One braid steel wire

Cover

Thermoplastic polymer, blue, non pinpricked, black ink-jet branding

Applications

- Water cleaning applications such as professional power washers
- Car-wash stations, including self-service car-wash stations

Features

- Rugged construction for HD application and prolonged lifetime
- Lightweight
- Compact design
- High flexibility
- Abrasion resistant

Description

High pressure service hose suitable for connection between water pump and washing gun. The steel reinforcement makes this hose extremely resistant but still lightweight if compared with rubber alternatives. The construction and the pressure rating of this hose make this product the ideal choice for professional power washers or self-service car-wash stations. Also available as factory made assemblies: please contact our sales office for further details

Temperature Range

-20°C to +60°C
(-4°F to +140°F)

Note

Available as factory made assemblies with/ or without box. Please contact our sales office for further details.

WARNING!

Not suitable for hot water or steam.
Max water temp 60°C/ 140°F

INDUSTRIAL
AUTOMATION

GAS

FUEL

CHEMICALS

WATER

POWER
WASH

ECOLOGY
SEWER
CLEANING

HORTITEC

WATER
DELIVERY

APPLICATIONS



MULTICOLOR



079

PACKAGING



Part No.	Hose size			ID		OD		WP		BP		Safety factor	Bend radius		Weight		Ferrule part no.	
	dash	inch	DN	mm	inch	mm	inch	bar	psi	bar	psi		mm	inch	g/m	lbs/ft	carbon	stainless
07B2	-4	1/4"	6	6,50	0,256	11,90	0,469	280	4000	1120	16000	4:1	40	1,57	160	0,108	SAC121	SAC821
07B3	-5	5/16"	8	8,10	0,319	13,60	0,535	210	3000	840	12000	4:1	55	2,17	190	0,128	SAC131	SAC831
07B4	-6	3/8"	10	9,80	0,386	16,10	0,634	210	3000	840	12000	4:1	65	2,56	245	0,165	SAC141	SAC841