



## Confirmation of Product Type Approval

**Company Name:** TRANSFER OIL S.P.A.

**Address:** VIA SACCA 64 COLORNO (PARMA) 43052 Italy

**Product:** Flexible Hose

**Model(s):** 041 - VHP 10000

**Endorsements:**

<b>Certificate Type</b>	<b>Certificate Number</b>	<b>Issue Date</b>	<b>Expiry Date</b>
Product Design Assessment (PDA)	20-2059594-PDA	15-JAN-2021	14-JAN-2026
Manufacturing Assessment (MA)	21-4770423	12-MAY-2021	16-MAY-2026
Product Quality Assurance (PQA)	NA	NA	NA

### **Tier**

3 - Type Approved, unit certification not required

### **Intended Service**

Marine and Offshore Applications - High Pressure Non-Flammable Hydraulic Fluid, Compressed Air, Fresh Water & Sea Water Systems

### **Description**

Thermoplastic polyester elastomer hoses reinforced with one or two braids of aramid fiber and one braid of steel wire reinforcement covered by thermoplastic polyurethane elastomer.

For details see Manufacturer's data sheets.

### **Ratings**

Sizes 1/4 and 3/8 inches

Working pressure 700 bar, Burst pressure 2800 bar.

Temperature Range: -40°C up to +100°C with the following exceptions:

Air: Tmax +70°C, Water based fluids: Tmax +70 °C

### **Service Restrictions**

1) Unit Certification is not required for this product. If the manufacturer or purchaser request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined.

2) The scope of Type Approval is to comply with MSC.1/Circ.1221 dated 11 December 2006.

3) Hoses are to be completed with factory assembled end fittings or factory supplied end fittings installed

in accordance with manufacturer's specifications.

4) End connections are to comply with applicable requirements and limitations of the Rules for the intended service (e.g. Rules for Building and Classing Marine Vessels 4-6-7/3.5.1)

5) Not to be used in piping systems for flammable media (regardless of flash point) and sea water systems where failure may result in flooding as per Rules for Building and Classing Marine Vessels 4-6-2/5.7.3(c).

6) Hose assemblies are to be installed only where flexibility is required and are not to be subject to torsional deflection under normal conditions; hose length is to be limited to that required by flexibility only.

7) Not to be installed in applications where large amount of repeated flexing is expected in combination with pressure pulses.

8) Not to be used in high pressure fuel oil injection systems, steam systems or oil supply lines to boilers.

9) For air services the hose cover must be pin pricked as per Manufacturer's recommendations.

10) Flexible hoses are to be permanently marked by the manufacturer with the following details: Hose manufacturer's name or trademark, Date of manufacture (month/year), Designation type reference, Nominal diameter, Pressure rating, Temperature rating.

### Comments

1) The Manufacturer has provided a declaration about the control of, or the lack of Asbestos in this product.

2) Manufacturer recommended fittings:

- Size 1/4 inches, manufacturer's fitting SAF 121 or SAF 821

- Size 3/8 inches, manufacturer's fitting SAF 141 or SAF 821

3) Any fluid, regardless of its flash point, liable to support a flame is to be treated as a flammable fluid. Aviation fuel, diesel fuel, heavy fuel oil, lubricating oil and hydraulic oil (unless the hydraulic oil is specifically specified as non-flammable) are all to be considered flammable fluids as per Rules for Building and Classing Marine Vessels 4-6-1/3.23.

### Notes, Drawings and Documentation

Drawing No. 0601, 3/16 OFF SHORE MASTER 5K, Revision: 0, Pages: 1

Drawing No. 0601 CR, 0601 CROSS SECTION, Revision: 0, Pages: 1

Drawing No. 0602, 1/4 OFF SHORE MASTER 5K, Revision: 0, Pages: 1

Drawing No. 0602 CR, 0602 CROSS SECTION, Revision: 0, Pages: 1

Drawing No. 0604, 3/8 OFF SHORE MASTER 5K, Revision: 0, Pages: 1

Drawing No. 0604 CR, 0604 CROSS SECTION, Revision: 0, Pages: 1

Drawing No. 0605, 1/2 OFF SHORE MASTER 5K, Revision: 0, Pages: 1

Drawing No. 0605 CR, 0605 CROSS SECTION, Revision: 0, Pages: 1

Drawing No. 0607, 3/4 OFF SHORE MASTER 5K, Revision: 0, Pages: 1

Drawing No. 0607 CR, 0607 CROSS SECTION, Revision: 0, Pages: 1

Drawing No. 0608, 1 OFF SHORE MASTER 5K, Revision: 1, Pages: 1

Drawing No. 0608 CR, 0608 CROSS SECTION, Revision: 0, Pages: 1

Drawing No. 1687, 3/4 OFF SHORE MASTER 3K, Revision: 1, Pages: 1

Drawing No. 1687 CR, 1687 CROSS SECTION, Revision: 0, Pages: 1

Drawing No. 1688, 1 OFF SHORE MASTER 3K, Revision: 1, Pages: 1

Drawing No. 1688 CR, 1688 CROSS SECTION, Revision: 0, Pages: 1

Drawing No. 1692, 1/4 OFF SHORE MASTER 10K, Revision: 0, Pages: 1

Drawing No. 1692 CR, 1692 CROSS SECTION, Revision: 0, Pages: 1

BURST TEST REPORT 0601 (Parma, Italy, 04-aug-2014)

BURST TEST REPORT 0602 (Parma, Italy, 09-apr-2014)

BURST TEST REPORT 0604 (Parma, Italy, 09-apr-2014)

BURST TEST REPORT 0605 (Parma, Italy, 09-apr-2014)

BURST TEST REPORT 0607 (Parma, Italy, 03-nov-2013)

BURST TEST REPORT 0608 (Parma, Italy, 17-jul-2014)

BURST TEST REPORT 1687 (Parma, Italy, 11-jun-2014)

BURST TEST REPORT 1688 (Parma, Italy, 20-jun-2013)

BURST TEST REPORT 1692 (Parma, Italy, 24-sep-2014)

Impulse test report CQ15029-0601 (Parma, Italy, 27-apr-2015)

Impulse test report CQ14062-0605 (Parma, Italy, 01-dec-2014)

Impulse test report CQ15009-0608 (Parma, Italy, 09-feb-2015)

Impulse test report CQ14043 - 1687 (Parma, Italy, 29-sep-2014)

Impulse test report CQ14038 - 1692 (Parma, Italy, 10-sep-2014)

Drawing No. TO Hydraulic Impulse test procedures, TO Hydraulic Impulse test procedures, Revision: 0, Pages: 1

### **Term of Validity**

This Product Design Assessment (PDA) Certificate remains valid until 14/Jan/2026 or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

### **ABS Rules**

2020 Rules for Conditions of Classification, 1-1-4/7.7 & 1-1-A3 and 1-1-A4, which covers the following:

2020 Rules for Building and Classing Marine Vessels 4-6-2/5.7

2020 Rules for High Speed Craft 1-1-4/11.9 & 1-1-A2 and 1-1-A3, which covers the following:

2020 Rules for High Speed Craft 4-4-1/9.19 except 9.19.3 (c)

2020 Rules for Conditions of Classification - Mobile Offshore Units, 1-1-4/9.7 & 1-1-A2 and 1-1-A3, which covers the following:

2020 Rules for Building and Classing Mobile Offshore Units 4-2-1/11.29

**International Standards**

NA

**EU-MED Standards**

NA

**National Standards**

NA

**Government Standards**

NA

**Other Standards**

NA



Corporate ABS Programs  
American Bureau of Shipping  
Print Date and Time: 10-Jul-2024 2:40

ABS has used due diligence in the preparation of this certificate, and it represents the information on the product in the ABS Records as of the date and time the certificate is printed.

If the Rules and/or standards used in the PDA evaluation are revised or if there is a design modification (whichever occurs first), a PDA revalidation may be necessary.

The continued validity of the MA is dependent on completion of satisfactory audits as required by the ABS Rules. The validity of both PDA and MA entitles the product to receive a **Confirmation of Product Type Approval**.

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or prior to the effective date of the ABS Rules and standards applied at the time of PDA issuance. ABS makes no representations regarding Type Approval of the Product for use on vessels, MODUs or facilities built after the date of the ABS Rules used for this evaluation.

Type Approval requires Drawing Assessment, Prototype Testing and assessment of the manufacturer's quality assurance and quality control arrangements. The manufacturer is responsible to maintain compliance with all specifications applicable to the product design assessment. Unless specifically indicated in the description of the product, certification under type approval does not waive requirements for witnessed inspection or additional survey for product use on a vessel, MODU or facility intended to be ABS classed or that is presently in class with ABS.

Due to wide variety of specifications used in the products ABS has evaluated for Type Approval, it is part of our contract that; whether the standard is an ABS Rule or a non-ABS Rule, the Client has full responsibility for continued compliance with the standard.

Questions regarding the validity of ABS Rules or the need for supplemental testing or inspection of such products should, in all cases, be addressed to ABS.