

# 130 Greasing

## Constant pressure thermoplastic hose for high pressure greasing applications

Up to 400 bar (5800 psi)



INDUSTRIAL  
AUTOMATION

GREASING

PUSH ON

GAS

FUEL

CHEMICALS

WATER

### FEATURES

#### Inner Tube

Polyester

#### Reinforcement

One braid of synthetic fiber

#### Cover

Anti-grip polyurethane non pinpricked (\*130C version is pinpricked)

#### Applications

- Manual and air-operated greasing guns
- Central greasing and lubrication systems

#### Features

- Polyester reinforcement for high pressure
- Extremely compact and Flexible
- Highly kink resistant
- Special anti sticky cover for easy installation and compact routing
- TPU cover guarantees anti-abrasion properties

#### Description

High pressure hose suitable for petroleum, synthetic or water based hydraulic fluids specifically designed for diverse greasing and lubrication applications of industrial vehicles and handheld or automatic greasing distribution equipment. Different versions to suit multiple fitting brands.

#### Temperature Range

-40°C to +60°C  
(-40°F to +140°F)

#### Specifications

Meets requirements of DIN 1283

### APPLICATIONS



### PACKAGING



Part No.	Hose size			ID		OD		WP		BP		Safety factor	Bend radius		Weight		Ferrule part no.	
	dash	inch	DN	mm	inch	mm	inch	bar	psi	bar	psi		mm	inch	g/m	lbs/ft	carbon	stainless
130A	-	5/32"	4	4	0,157	9,7	0,382	400	5800	1000	14500	2,5:1	35	1,378	70	0,047	SAA101	SAA801
130C	-	5/32"	4	4	0,157	8,30	0,327	400	5800	1000	14500	2,5:1	25	0,98	46	0,030	SAB101	SAB801