

# 184 LPG applications

INDUSTRIAL  
AUTOMATION

**Thermoplastic hose for LPG applications**  
Up to 30 bar (435 psi)

GAS

FUEL



## FEATURES

CHEMICALS

### Inner Tube

Polyamide PA6

### Reinforcement

One braid of synthetic fiber

### Cover

Polyurethane, black, pinpricked, white ink-jet branding

WATER

### Applications

- Low pressure hose suitable for LPG applications

### Features

- Polyamide 6 tube construction compatible with LPG
- Non metallic design with bonded construction
- Lightweight and flexible
- Antiabrasion cover for optimum wear resistance
- Pinpricked cover.

### Description

Low pressure hose with black antiabrasion cover suitable for LPG applications. Non metallic lightweight design for easy handling and manipulation.

### Temperature Range

-40°C to +100°C  
(-40°F to +212°F)

## APPLICATIONS



## PACKAGING



## CERTIFICATION

Part No.	Hose size			ID		OD		WP		BP		Safety factor	Bend radius		Weight		Ferrule part no.	
	dash	inch	DN	mm	inch	mm	inch	bar	psi	bar	psi		mm	inch	g/m	lbs/ft	carbon	stainless
1841	-3	3/16"	5	5	0,197	8,2	0,323	30	435	150	2175	5:1	25	0,984	60	0,040	SAB111	SAB811
1842	-4	1/4"	6	6,5	0,256	10,2	0,402	30	435	150	2175	5:1	35	1,378	90	0,060	SAB121	SAB821