



TRANSFER OIL

Pure Fluid Attitude



118 - ECOLOGY 3000 LT

Constant pressure thermoplastic hose for high pressure lateral sewer cleaning applications up to 210 bar (3000 psi)



FEATURES

Inner Tube

Polyester elastomer

Reinforcement

Two braids of synthetic fiber

Cover

Polyurethane - black - pinpricked - laser branding

Applications

Compact sewer cleaning vehicles and equipment for cleaning smaller residential commercial and industrial lateral sewer lines used as connection to the main sewer line

Features

Abrasion resistant - Compact - Lightweight and extremely flexible - Kink resistant - 2 polyester braid design - Black cover resistant to humid working conditions to increase lifetime

Description

Hose suitable for lateral cleaning applications requiring high pressure performance and high flexibility for cleaning the smaller sewer pipes. Also available as factory made assemblies; please contact our sales office for further details

Temperature Range

-40 °C to 60 °C (-40 °F to 140 °F)

Standard Branding

TRANSFER OIL - TO INDUSTRIAL - Part No - ECOLOGY 3000 LT - LATERAL SEWER CLEANING HOSE - Inch Size - DN Size - WP bar / psi - MADE IN ITALY - www.transferoil.com - QQ/YY - Batch No

| Part no. | DN | Inches | Dash | ID (mm) | OD (mm) | WP (bar) | BP (bar) | ID (inch) | OD (inch) | WP (psi) | BP (psi) | SF | BR (mm) | BR (inch) | Weight (gr/m) | Weight (lb/ft) | Ferrule standard | Ferrule A316L |
|----------|------|--------|------|---------|---------|----------|----------|-----------|-----------|----------|----------|-------|---------|-----------|---------------|----------------|------------------|---------------|
| 1184 | DN10 | 3/8 | -6 | 9.7 | 16.0 | 210 | 525 | 0.382 | 0.630 | 3000 | 7500 | 2.5:1 | 55 | 2.17 | 149 | 0.100 | SAB141 | SAB841 |
| 1185 | DN12 | 1/2 | -8 | 13.0 | 20.3 | 210 | 525 | 0.512 | 0.799 | 3000 | 7500 | 2.5:1 | 75 | 2.95 | 222 | 0.149 | SAB151 | SAB851 |

Hose assembly - With hose reel

| part no | description | fittings |
|---------|----------------------|---------------------------|
| ESCXXX | 3/8" ECOLOGY 3000 LT | 3/8" M/F BSP |
| ESDXXX | 3/8" ECOLOGY 3000 LT | 3/8" M/M NPT |
| ESOXXX | 3/8" ECOLOGY 3000 LT | 3/8" M/F BSP - AISI A316L |
| ESPXXX | 3/8" ECOLOGY 3000 LT | 3/8" M/M NPT - AISI A316L |
| ETEXXX | 1/2" ECOLOGY 3000 LT | 1/2" M/F BSP |

| | | |
|--------|----------------------|---------------------------|
| ETFXXX | 1/2" ECOLOGY 3000 LT | 1/2" M/M NPT |
| ETQXXX | 1/2" ECOLOGY 3000 LT | 1/2" M/F BSP - AISI A316L |
| ETRXXX | 1/2" ECOLOGY 3000 LT | 1/2" M/M NPT - AISI A316L |

XXX= total length of the assembled hose in meters (1mt = 3,28 ft)

Hose assembly - Without hose reel

| part no | description | fittings |
|---------|----------------------|---------------------------|
| FSCXXX | 3/8" ECOLOGY 3000 LT | 3/8" M/F BSP |
| FSDXXX | 3/8" ECOLOGY 3000 LT | 3/8" M/M NPT |
| FSOXXX | 3/8" ECOLOGY 3000 LT | 3/8" M/F BSP - AISI A316L |
| FSPXXX | 3/8" ECOLOGY 3000 LT | 3/8" M/M NPT - AISI A316L |
| FTEXXX | 1/2" ECOLOGY 3000 LT | 1/2" M/F BSP |
| FTFXXX | 1/2" ECOLOGY 3000 LT | 1/2" M/M NPT |
| FTQXXX | 1/2" ECOLOGY 3000 LT | 1/2" M/F BSP - AISI A316L |
| FTRXXX | 1/2" ECOLOGY 3000 LT | 1/2" M/M NPT - AISI A316L |

XXX= total length of the assembled hose in meters (1mt = 3,28 ft)

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.

Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.

Document date: 31/03/2025

www.transferoil.com