



TRANSFER OIL

Pure Fluid Attitude



226 - 6SWHX HELIX

Thermoplastic multispiral hose for UHP water based applications from 2500 to 3050 (from 36200 to 44200 psi)



FEATURES

Inner Tube

Polyoxymethylene (POM)

Reinforcement

Six spiral layers of higher tensile steel wire

Cover

Special Polyester Copolymer, non pinpricked, black ink-jet branding

Industrial Applications

Waterjet cutting. Tube cleaning, surface preparation and paint removal. Hydro demolition. Ships, tanks and vessel cleaning. Waterblast supply hose. General industrial cleaning. Removal of accumulated dirt from surfaces.

Hydraulic Applications

Hydraulic jacks // Bolt tensioning // Testing applications // General UHP hydraulic applications

Hydraulic Applications

Ultra high working pressure // Excellent chemical resistance // Resistance to ozone, ultraviolet light and aging // High resistance against abrasion // Low volumetric expansion at maximum working pressure // Resistant to sea water // High impulse resistance // Long length capability // Excellent cut and crush resistance

Temperature Range

Ultra High Pressure hose utilising high tensile steel wire applied in counter rotating multiple spiral layers. Tube and cover of engineering polymer with intermediate adhesion layers.

Available As Factory Made Assemblies: Please Contact Our Sales Office For Further Details.

Description

-30°C to 70°C (-22°F to 158°F)

Standard Branding

TRANSFER OIL - HELIX® - TO UHP - Part No - 6SWHX - Inch Size - DN Size - WP bar / psi - SKIVE MADE IN ITALY - www.transferoil.com - Batch No

| Part no. | DN | Inches | Dash | ID (mm) | OD (mm) | WP (bar) | BP (bar) | ID (inch) | OD (inch) | WP (psi) | BP (psi) | SF | BR (mm) | BR (inch) | Weight (gr/m) | Weight (lb/ft) | Ferrule standard | Ferrule A316L |
|----------|------|--------|------|---------|---------|----------|----------|-----------|-----------|-----------|----------|-------|---------|-----------|---------------|----------------|------------------|---------------|
| 2261 | DN5 | 3/16 | -3 | 4.8 | 13.2 | 3050 | 7000 | 0.189 | 0.520 | 4420 0 | 101600 | 2.3:1 | 210 | 8.27 | 450 | 0.302 | HAF111 | HAF811 |
| 2263 | DN8 | 5/16 | -5 | 7.6 | 19.1 | 3050 | 7000 | 0.299 | 0.752 | 4420 0 | 101600 | 2.3:1 | 250 | 9.84 | 1087 | 0.730 | HAH131 | |
| 2265 | DN12 | 1/2 | -8 | 12.8 | 26.0 | 2500 | 6250 | 0.504 | 1.024 | 36200 | 90500 | 2.5:1 | 350 | 13.78 | 1782 | 1.197 | HAH151 | HAH851 |

WJTA-IMCA Color Coding Scheme for Pressure Hoses - Maximum Working Pressure Applicable

* The safety factor between the burst pressure and working pressure depend on the application requirements. Four to one (4:1) safety factor should be used in dynamic impulsing hydraulic applications.

** The maximum WORKING PRESSURE of an assembly is given by the component having the lowest working pressure.
This means that if the working pressure of a fitting is lower than the working pressure of the hose, the WORKING PRESSURE of the fitting becomes the WORKING PRESSURE of the entire assembly.
The maximum WORKING PRESSURE of the assembly can be found marked on each sleeve of the assembly and on the pressure test report.

AVAILABLE INSERTS

| Part | Dash | Inch | DN | F-BSPP | F-DKOS | F-HP | F-MET24-60 | F-TYPE | M-HP | M-HP-MET | M-MP |
|------|------|------|------|--------|--------|------|------------|--------|------|----------|------|
| 2261 | -3 | 3/16 | DN5 | HBI | | HGI | HCI | HFI | HMI | HNI | |
| 2263 | -5 | 5/16 | DN8 | | HDI | | | HFI | HMI | HNI | HLI |
| 2265 | -8 | 1/2 | DN12 | | HDI | | | HFI | HMI | HNI | |

*Dimensions and values shown may be changed without prior notice to improve product performances and reliability.
Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.
Document date: 03/12/2024
www.transferoil.com*