




TRANSFER OIL

Pure Fluid Attitude



Male HP | Female HP



Part no.	Description	Side A	Side B	ID	HEX	L	MAWP
D9HMB 04FB04 01	1/4 M-HP F-HP 1/4 60k 316D	1/4	1/4	2.1	3/4 19	35	60k
D9HMB 04FB06 01	1/4 M-HP F-HP 3/8 60k 316D	1/4	3/8	2.1	1 26	38	60k
D9HMB 04FB09 01	1/4 M-HP F-HP 9/16 60k 316D	1/4	9/16	2.1	1+3/8 35	43	60k
D9HMB 06FB04 01	3/8 M-HP F-HP 1/4 60k 316D	3/8	1/4	2.4	13/16 21	41	60k
D9HMB 06FB06 01	3/8 M-HP F-HP 3/8 60k 316D	3/8	3/8	3.2	1 26	44	60k
D9HMB 06FB09 01	3/8 M-HP F-HP 9/16 60k 316D	3/8	9/16	3.2	1+3/8 35	49	60k
D9HMB 09FB04 01	9/16 M-HP F-HP 1/4 60k 316D	9/16	1/4	2.4	1+3/16 30	44	60k
D9HMB 09FB06 01	9/16 M-HP F-HP 3/8 60k 316D	9/16	3/8	3.2	1+3/16 30	47	60k
D9HMB 09FB09 01	9/16 M-HP F-HP 9/16 60k 316D	9/16	9/16	4.8	1+3/8 35	52	60k
D9HMB 09FR18 01	9/16 M-HP F-HP M18 60k 316D	9/16	M18	4.8	1+1/2 38	54	60k

Dimensions and values shown may be changed without prior notice to improve product performances and reliability.

Transfer Oil S.p.A. assumes no liability on mistakes nor errors appearing in this spec sheet.

Document date: 31/03/2025

www.transferoil.com